



We offer up to 100 rounds cartridge vessel for all industrial needs application with unique spring aided design opening mechanism make changing cartridge so easy that can be handled by one person

PRODUCT SPECIFICATION

- 1 Unique design able to fit either DOE (double open end) or SOE with “222” configuration.
- 1 Max Operating pressure – 10 Bar at 25 Deg C Inlet/Outlet Connection – 3- 12” ANSI Flange
- 1 Vent/Drain - 1” NPT
- 1 O Ring – EPDM, Viton or Telfon encapsulated Viton
- 1 Connection Option - DIN, JIS10K Flange, BSP coupling or others.
- 1 Material – Carbon Steel, SS304, SS316 & SS316L
- 1 Smooth Bead blasted finishing for easy cleaning, electro-polishing is optional

ORDERING INFORMATION

FT-HCF Model	12- No. Of Cartridge	40 - Cartridge Length	A - Material	10 - Design Pressure	030- Pipe Connection	A – Connection Type	SA- Cover Closure Type	M Suffix
FT-HCF	5	20 = 20"	A - SS304	10 Bar	2" to 24"	A - ANSI	DL - Davit Lid	M - Modification
	7	30 = 30"	AL - SS304L	16 Bar		D - DIN	SA - Spring Aided	
	9	40 = 40"	S - SS316	Other pressure on request		J - JIS	SB - Spring Balancer	
	10	50 = 50"	SL - SS316L				SV - Quick opening	
	12		CS - Carbon Steel					
	16 20 and onwards							

Filtrex Technology Pte Ltd

* 4009 Ang Mo Kio Ave 10, #04-37 TECHplace 1, Singapore 569738

| +65 6456 2388 | 7 : +65 6456 8266

Email : info@filtrex-tech.com | Website : www.filtrex-tech.com